

MAGNETS FOR HOLDING & STORAGE

PORTABLE MAGNETIC HOLDERS

Secure brooms, flashlights, spray cans, markers, etc. to any steel surface without drilling to install clips/holders. These powerful permanent magnets are quickly installed and repositioned when needed. Keep critical tools for the job handy.



Style	Max Hold - lbs (kg)	Description	Application	Magnet O.D. (in)	Opening (in)	Magnet I.D. (in)	OAH (in)	Wt. (lbs)	Model No.	
A	15.0 (6.80)	Nickel Plated Clamp	Spring Tension	Ceramic	1.24	0.19 – 0.38	0.25	0.88	0.05	MX1000NP01
A	25.0 (11.34)	Nickel Plated Clamp	Spring Tension	Ceramic	1.41	0.31 – 0.75	0.375	1.53	0.10	MX1500NP01
A	42.0 (19.05)	Nickel Plated Clamp	Spring Tension	Ceramic	2.03	0.63 – 1.25	0.859	2.31	0.19	MX2000NP01
A	80.0 (36.29)	Nickel Plated Clamp	Spring Tension	Ceramic	2.63	1.00 – 1.88	1.00	2.50	0.41	MX2500NP01
A	15.0 (6.80)	Stainless Steel Clamp	Spring Tension	Ceramic	1.24	0.38 – 0.50	0.25	1.09	0.05	MX1000SS01
A	25.0 (11.34)	Stainless Steel Clamp	Spring Tension	Ceramic	1.41	0.63 – 0.88	0.375	1.91	0.11	MX1500SS01
A	25.0 (11.34)	Stainless Steel Clamp	Spring Tension	Ceramic	1.41	0.88 – 1.13	0.375	2.03	0.10	MX1500SS02
A	25.0 (11.34)	White Plastic Coated Clamp	Spring Tension	Ceramic	1.41	0.31 – 0.75	0.375	1.66	0.10	MX1500WP03
A	42.0 (19.05)	White Plastic Coated Clamp	Spring Tension	Ceramic	2.03	0.63 – 1.25	0.859	2.31	0.19	MX2000WP01
A	80.0 (36.29)	White Plastic Coated Clamp	Spring Tension	Ceramic	2.63	1.00 – 1.88	1.00	2.88	0.41	MX2500WP01
B	42.0 (19.05)	Black Vinyl Coated Clamp	Flashlight	Ceramic	2.03	1.50 – 1.88	0.859	2.19	0.19	MX2000VB02
C	15.0 (6.80)	Zinc Plated Clamp	Spring Tension	Ceramic	1.24	0.38 – 0.63	0.25	1.13	0.06	MX1000ZP01
C	25.0 (11.34)	Zinc Plated Clamp	Spring Tension	Ceramic	1.41	0.75 – 1.13	0.375	1.53	0.13	MX1500ZP01
C	25.0 (11.34)	Zinc Plated Clamp	Spring Tension	Ceramic	1.41	1.00 – 1.50	0.375	1.53	0.19	MX1500ZP02
C	15.0 (6.80)	Black Vinyl Coated Clamp	Spring Tension	Ceramic	1.24	0.38 – 0.63	0.25	1.13	0.06	MX1000VB01
C	25.0 (11.34)	Black Vinyl Coated Clamp	Spring Tension	Ceramic	1.41	0.75 – 1.13	0.375	1.53	0.13	MX1500VB01
C	19.0 (8.62)	Black Vinyl Coated Clamp	Spring Tension	Ceramic	2.03	2.00 – 2.50	0.859	2.31	0.22	MX2000VB01
D	15.0 (6.80)	Black Plastic Clamp	Non-Conductive	Ceramic	1.24	0.87 – 1.13	0.25	0.98	0.05	MX1000BP01
D	25.0 (11.34)	Black Plastic Clamp	Non-Conductive	Ceramic	1.41	1.13 – 1.38	0.375	1.25	0.10	MX1500BP01
D	42.0 (19.05)	Black Plastic Clamp	Non-Conductive	Ceramic	2.03	1.87 – 2.13	0.859	2.06	0.20	MX2000BP01
E	42.0 (19.05)	Red Vinyl Hook	Broom Holder	Ceramic	2.03	1.38	0.859	4.50	0.20	MX2000RV01
F	80.0 (36.29)	Black Rubber Spring Clamp	Broom Holder	Ceramic	2.63	0.87 – 1.25	1.00	1.50	0.65	MX2500BH01
F	N/A	Black Rubber Spring Clamp	Broom Holder	N/A	N/A	0.87 – 1.25	2.62"L x 1.25"W x 1.50"H	0.20		981113

TWO LINE CLAMPS



Instantly install magnetic clamps on any steel surface. No drilling or other mounting hardware needed. Idea for pneumatic lines, PVC lines and electrical wires. Perfect for holding forklift battery cables and connector in place. Bright plated permanent magnet and black polypropylene holder withstand moisture. Temperature range is -20° to 190°F.



ID (in)	Hold - Lbs (kg)	Dia (in)	Projects (in)	Weight (lb)	Model No.	ID (in)	Hold - Lbs (kg)	Dia (in)	Projects (in)	Weight (lb)	Model No.
1/4	25 (11.34)	1.41	1-1/4	0.10	TLC0250M	3/8	63 (28.57)	2.03	1-1/4	0.15	TLCS0375R
3/8	42 (19.05)	2.03	1-1/4	0.15	TLC0375M	1/2	63 (28.57)	2.63	1-3/4	0.40	TLCS0500R
1/2	80 (36.29)	2.63	1-3/4	0.40	TLC0500M	5/8	63 (28.57)	2.63	1-3/4	0.40	TLCS0625R
5/8	80 (36.29)	2.63	1-3/4	0.40	TLC0625M						

TOOL STORAGE HOLDING TRAYS



These Tool Storage Holding Trays are used for holding tools, fasteners, spray cans, tape, etc. to the sides of tool boxes, walls, tables or any area where tools need to be within reach. The Magnetic Mount tray allows you to quickly remove the tray from your toolbox and take it wherever your tools are needed. No need to run back and forth to your toolbox. Most standard size tool boxes will hold two, ST0625 trays, side by side.

FEATURES:

- » Sturdy one-piece Stainless Steel construction
- » Direct Mount or Magnetic Mount option
- » Tray depth one inch (1") on all models
- » Direct mount models have 2 or 3 thru-holes

Magnetic Mount					
Hold - lbs (kg)	Height (in)	Length (in)	Projects (in)	Weight (lbs)	Model No.
20.5 (9.29)	4.25	6.25	2.75	1.25	ST0625M
43.5 (19.73)	4.25	11.50	2.75	2.30	ST1150M
43.5 (19.73)	4.25	14.00	2.75	2.45	ST1400M

Through Hole Mount					
Mounting Hole - in (mm)	Height (in)	Length (in)	Projects (in)	Weight (lbs)	Model No.
0.201 (5.11)	4.25	6.25	2.75	0.95	ST0625
0.201 (5.11)	4.25	11.50	2.75	1.70	ST1150
0.201 (5.11)	4.25	14.00	2.75	1.85	ST1400

